

The Flo-More FMRC-2D6S Series



Applications: Sift/Scalp/Scalp, Sift/Sift/Scalp, Scalp/Scalp/Scalp Grains, Seeds, Pellets and other Bulk Commodities

Capacity: Models available from 1,000 to 10,000 bushels per hour

Technical Specifications FMRC-2D6S-5,000:

Extreme Height	68"	Motors:	Two 5HP, 3 Phase, 230/460/60HZ
Extreme Width	83"		Available in 1 Phase and 50HZ
Extreme Length	210"	Drives:	Two Gear Reducers
Weight	5,500 pounds	Options:	Aspiration available upon request, Multiple Hoppers or Common Discharge

Features:

- Dual Drums, Six Screens
- Total Screen Area –175.93 Ft²
- Sift/Scalp/Scalp, Sift/Sift/Scalp or Scalp/Scalp/Scalp Screen arrangements
- Mild Steel Materials of Construction
- 3/16 Plate Clean Grain Discharge Hoppers
- 3/16 Plate Inlet
- Cleaner Door Panel is 12 Gauge M.S.
- Conveyance Auger Shaft is 6" Schedule 80
- Auger Flights of 7 Gauge M.S. - 28" Diameter
- Screens are 28 inch ID x 48 inches long
- Heavy-duty Bearings and Supports
- Two - 5 HP Motors – 3/60/230-460
- Two - Gear Reducer Drive
- Adjustable Brush type screen cleaning
- Sheaves, Belts and OSHA-Type Drive Guards
- Completely Assembled & Tested in Shop
- Painted Ross Gray unless otherwise specified

Flo-More Products are designed and manufactured by:

Ferrell-Ross Roll Manufacturing Inc.

3690 FM2856, Hereford, Texas 79045 U.S.A.

T: 806-364-9051

F: 806-364-8853

E: sales@ferrellross.com

W: www.ferrellross.com